

**Liste des références pour :
Ecran LCD industriel 4/3 intégrable par l'arrière**

Modèle	Diagonale d'affichage	Résolution	Luminosité	Type de rétroéclairage	Contraste	Angle de vue (H/V)
OF0576-VN40LO	5,7"	640 x 480	400 cd/m ²	LED	800:1	160 / 140
OF0656-VN40LO	6,5"	640x480	400 cd/m ²	LED	600:1	160 / 140
OF0846-SN35LO	8,4"	800x600	350 cd/m ²	LED	600:1	161 / 140
OF0975-XN35LO	9,7"	1024x768	350 cd/m ²	LED	500:1	140 / 130
OF1045-SN35CO	10,4"	800x600	350 cd/m ²	CCFL	600:1	140 / 120
OF1045-SN35LO	10,4"	800x600	350 cd/m ²	LED	600:1	141 / 120
OF1045-XN35LO	10,4"	1024x768	350 cd/m ²	LED	600:1	160 / 140
OF1205-SN40CO	12,1"	800x600	400 cd/m ²	CCFL	600:1	140 / 120
OF1205-SN25LO	12,1"	800x600	250 cd/m ²	LED	600:1	140 / 120
OF1205-XN18CO	12,1"	1024x768	180 cd/m ²	CCFL	500:1	80 / 65
OF1205-XN20LO	12,1"	1024x768	200 cd/m ²	LED	500:1	90 / 65
OF1205-XN35LO	12,1"	1024x768	350 cd/m ²	LED	550:1	160 / 140
OF1505-XN25CO	15"	1024x768	250 cd/m ²	CCFL	450:1	130 / 110
OF1505-XN25LO	15"	1024x768	250 cd/m ²	LED	700:1	140 / 120
OF1705-EN30CO	17"	1280x1024	300 cd/m ²	CCFL	800:1	170 / 160
OF1705-EN25LO	17"	1280x1024	250 cd/m ²	LED	800:1	170 / 160
OF1905-EN30CO	19"	1280x1024	300 cd/m ²	CCFL	800:1	170 / 160
OF1905-EN25LO	19"	1280x1024	250 cd/m ²	LED	800:1	170 / 160
OF2005-UN30CO	20,1"	1600x1200	300 cd/m ²	CCFL	800:1	178 / 178
OF2005-UN40LO	20,1"	1600x1200	400 cd/m ²	LED	800:1	178 / 178
OF2316-UN40LO	23,1"	1600x1200	400 cd/m ²	LED	600:1	160 / 160

